



DEL MOTORIZED SOLUTIONS

(866) 44MOTOR - (215) 639.3880

WWW.MOTORIZEDSOLUTIONS.COM

(AC) Interface

Electrical Specifications:

Input:

Line Voltage: 115VAC +/- 20%

Low Voltage: Dry Contact - 0vac

Output:

Up to 115VAC 6A 1/3 HP

Mechanical Specifications:

L: 2.6" W: 2.1" H: .875"

Application Notes:

- Compact AC motor control module for 115vac and 230vac motors.
- Universal mount allows for placement in many locations and allows for maximum job site flexibility. Installations could range from a single gang junction box, a location in a headrail or even large central panels that are custom built for a project.
- 60 Programmable channels: provides one-touch control of individual motors, sub-groups of motors and ALL motors.
- System programming is achieved from many different devices.
- Programmable action features include:
 - Maintained or Momentary motor action
 - SPDT and SPST manual switch input, or X-10 control
 - Lamp control
 - Magnet Reed Switch as an over-ride
 - Wind features for any application
- Commands can be sent to our interface from many sources.

Command Sources could be:

- IR Remote Transmitters
- RF Remote Transmitters
- IR Key Pads
- RF Key Pads
- Standard Wall Switches (any type)
- Sun Sensors
- Timers.
- AV System (RS232 and or Contact Closure)
- Any Computer
- 12V trigger

Showroom:

2075 Byberry Road
The Atrium, Suite 108
Bensalem, PA 19020

Factory:

111 Buck Road
Unit #900
Huntingdon Valley, PA 19006