



DEL MOTORIZED SOLUTIONS

(866) 44MOTOR - (215) 639.3880

WWW.MOTORIZEDSOLUTIONS.COM

(DC) Interface

Electrical Specifications:

Input:

DC Voltage: 11VDC to 44VDC

Low Voltage: Dry Contact - 0vac

Output:

11 - 44VDC 5 FLA

Mechanical Specifications:

L: 2.94" W: 1.625" H: .875"

Application Notes:

- Compact DC motor control module for 12VDC to 24VDC motors.
- "A", or Automotive, applications are possible for installations in RV's.
- Universal mount allows for placement in many locations and allows for maximum job site flexibility. Installations could range from a single gang junction box, a location in a headrail or even large central panels that are custom built for a project.
- 60 Programmable channels: provides one-touch control of individual motors, sub-groups of motors and ALL motors.
- System programming is achieved from many different devices.

Programmable features include:

- Maintained or Momentary motor action
- SPDT and SPST manual switch input, or X-10 control
- Intermediate stops that are user defined via load sensing - great for Silhouette's
- Magnetic Reed Switch as an over-ride

Command Sources could be:

- IR Remote Transmitters ·RF Remote Transmitters
- IR Key Pads ·RF Key Pads
- Standard Wall Switches (any type)
- Dry Contacts (any type)
- Sun and Wind
- RS232 systems such as Crestron, Vantage, Lite Touch, Lutron or AMX
- IP sources

Total Motor load must NOT exceed 5Amps

Showroom:
2075 Byberry Road
The Atrium, Suite 108
Bensalem, PA 19020

Factory:
111 Buck Road
Unit #900
Huntingdon Valley, PA 19006



DEL MOTORIZED SOLUTIONS

(866) 44MOTOR - (215) 639.3880

WWW.MOTORIZEDSOLUTIONS.COM

Showroom:
2075 Byberry Road
The Atrium, Suite 108
Bensalem, PA 19020

Factory:
111 Buck Road
Unit #900
Huntingdon Valley, PA 19006